

## JC PEACOCK & CO LTD – PRODUCT SPECIFICATION SHEET Page1/1

## PURE DRIED VACUUM SALT

Pure Dried Vacuum Salt is ideal for a wide range of applications including food, animal feed, water treatment and chemical manufacture. The manufacturing plant is registered for food production, and food grade PDV certified to the BRC Global standard for food safety and feed grade PDV certificated to the Feed Materials Assurance Scheme, FEMAS. Low sulphate, bromide and moisture levels contribute to the high chemical purity which is required for most industrial applications. This purity is assured by a Quality Management System registered to ISO 9001 and a commitment to continuous improvement.

## CHEMICAL SPECIFICATION

Test methods used are as given in BS998:1990 or equivalent, except appearance which is a visual assessment.

| COMPONENT UNIT                               | SPECIFICATION                      | TYPICAL<br>ANALYSIS |
|--|------------------------------------|---------------------|
| Appearance                                   | Predominantly<br>White Crystalline |                     |
| Assay (dry basis) %m/m NaCl                  | 99.9 min.                          | 99.9                |
| Sodium Content %m/m Na                       | >39                                | 39.3                |
| Surface Moisture %m/m H <sub>2</sub> O       | 0.05 max.                          | 0.01                |
| Insoluble matter mg/kg                       | <50                                | <10                 |
| Alkalinity mg/kg Na₂CC                       | O₃ <150                            | 62                  |
| Sulphate mg/kg Na₂SC                         | O <sub>4</sub> <500                | 175                 |
| E535, Sodium                                 |                                    |                     |
| Hexacyanoferrate II mg/kg Na <sub>4</sub> Fe | e(CN)6 14 max.                     | 8.1                 |
| Total Iron mg/kg Fe                          | <5                                 | 1.5                 |
| Total Calcium mg/kg Ca                       | <20                                | 3.1                 |
| Total Magnesium mg/kg Mg                     | <5                                 | 0.7                 |
| Total Copper mg/kg Cu                        | 2 max.                             | <0.1                |
| Total Arsenic mg/kg As                       | 0.3 max.                           | <0.01               |
| Total Lead mg/kg Pb                          | 1 max.                             | <0.1                |
| Total Cadmium mg/kg Cd                       | 0.2 max.                           | <0.01               |
| Total Mercury mg/kg Hg                       | 0.05 max.                          | < 0.03              |
| Total Nickel mg/kg Ni                        | 0.75 max.                          | < 0.05              |
| Total Chromium mg/kg Cr                      | 0.75 max.                          | < 0.03              |
| Total Selenium mg/kg Se                      | 2.6 max.                           | <0.2                |
| Total Antimony mg/kg Sb                      | 2.6 max.                           | <0.2                |
| Total Bromide mg/kg Br                       | <150                               | 83                  |

## PHYSICAL CHARACTERISTICS

| Typical Pouring Density | 1.25 - 1.30 g/c | 1.25 - 1.30 g/cm₃ |  |
|-------------------------|-----------------|-------------------|--|
| Typical Sieve Analysis  | BS410 ref.      | % Through Sieve   |  |
|                         | 16 (1000µm)     | 99.9              |  |
|                         | 22 (710µm)      | 99.7              |  |
|                         | 30 (500µm)      | 92.6              |  |
|                         | 52 (300µm)      | 28                |  |
|                         | 85 (180µm)      | 4.8               |  |
|                         |                 |                   |  |

Country of Origin: England

Signed: STACEY KEATING – QUALITY COORDINATOR

JC PEACOCK & COMPANY LTD, NORTH HARBOUR, AYR, KA8 8AE - TEL 01292 292 000 - FAX 01292 292 001

**Important Note**: The information contained in this document is given in good faith and is to the best of suppliers Knowledge correct at the date of publication, but it is for the users to satisfy themselves of the suitability of the product for their purpose.